ForeFront® HL Herbicide

Supplement to Bulk Storage and Handling Guide

General Storage Comments

ForeFront HL herbicide is a combination of aminopyralid and 2,4-D. It handles well in bulk. The product requires no special mixing; has no restrictions related to flash point, and is compatible with most common materials of construction.

CAUTION: Eye contact may cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur. Read the label and MSDS for more information.

Product Density vs. Temperature

Temperature °F (°C)	20 (-7)	30 (-1)	40 (4)	50 (10)	60 (16)	70 (21)	80 (27)	90 (32)
Density (lb./gal.)		9.94	9.91	9.88	9.85	9.82	9.79	9.76

Flash Point, NFPA Rating, Storage Temperature, and Signal Word

Flash Point ¹ °F (°C)	NFPA 704 Diamond Ratings			Min. Storage Temperature °F (°C)	EPA Signal Word	
	Health	Flammability	Reactivity	, ,		
>200 (>93)	1	1	0	None Reported	Danger	

Material / Product Compatibility	Rating	Comment
Stainless Steel	ОК	Essentially non-corrosive
Mild Steel	ОК	Trace of corrosion
Buna-N, Neoprene, EPDM, Teflon	ОК	Little to no effect
Polyethylene (Cross-linked, Low & High Density, HMW), Polypropylene, Rigid PVC	OK	Little to no effect
Silicone Rubber, Viton, Nylon 6/6	ОК	Swells slightly
Plasticized PVC	Caution	Shrinks moderately
Aluminum, Copper, Yellow Brass	Caution	Slightly corrosive
Vellumoid	NO	Swells moderately. Severe weight gain
Tin, Zinc	NO	Moderate to severe corrosion

¹ The flash point of a liquid is the minimum temperature at which it gives off sufficient vapor to form an ignitable mixture with the air near the surface of the liquid or within the test vessel used.

Date Written: 07/13/2020 V0 Country: USA Page | 1

ForeFront® HL Herbicide

Supplement to Bulk Storage and Handling Guide

Bulk Tank N	Naterial of Construction and Requirements			
Material of Construction	Stainless steel is preferred. If state and local laws permit, existing polyethylene storage tanks may be utilized if the tank is free of cracks, UV degradation or other signs of aging or structural defects. Corteva will not bear risk or liability associated with the use of polyethylene bulk tanks.			
Venting Requirements	No special venting requirements.			
Couplers	Standard 2" Kamlok Style Adapter with cap for receiving bulk deliveries.			
Mixing Requirement	Does not require mixing under normal storage.			
Refillable C	ontainer Handling			
DOT / EPA	This product is regulated by US Department of Transportation for certain volumes and modes. See the Transportation section of the MSDS. Use only UN/DOT approved containers.			
Material of Construction	Stainless steel or polyethylene. Fluorination is not required.			
Mixing	Does require mixing under normal storage.			
Couplers	Standard couplers.			

NOTICE: The information, procedures, methods, and recommendations herein are presented in good faith and are believed to be accurate and reliable as of the publication date, but may well be incomplete and/or not applicable to all conditions or situations. No representation, guarantee, or warranty is made as to the accuracy, reliability, or completeness of said information, procedures, methods, and recommendations. Nor is any representation, guarantee, or warranty made that application or use of any of the same will avoid hazards, accidents, losses, damages, or injury of any kind to persons or property, or give desired results, or that the same will not infringe patents of Dow AgroSciences, DuPont or Pioneer and their affiliated companies. Readers must satisfy themselves as to the suitability of said information, procedures, methods, and recommendations prior to use.

Trademark of Dow AgroSciences, DuPont or Pioneer and their affiliated companies or respective owners.

ForeFront HL is not registered for sale or use in all states. Contact your state pesticide regulatory agency to determine if a product is registered for sale or use in your state.



Rev. 08/2020

Date Written: 07/13/2020 V0 Country: USA P a g e | **2**